



- High adhesive strength, stable shape, cannot be over-stretched
- Colour matched to the facade membrane
- Withstands three months of exposure to the weather

**Delivery form**

	Box weight [kg]	Roll length [m]	Roll width [mm]	Box contents [units]
PAVAFIX 60	2.8	25	60	4
PAVAFIX 20_40	2.8	25	60	4
PAVAFIX 150	3.2	25	150	2

**Field of application**



**Technical data**

Material	Pure acrylic adhesive on a plastic carrier
Thickness [mm]	0.3
Minimum installation temperature for base and air [°C]	-5
only with PAVAPRIM [°C]	-10
Installation temperature Tape [°C]	-5 to +40
Temperature resistance [°C]	-40 to +90

**Product description**

PAVAFIX is an all-round acrylate adhesive tape for permanent sealing of PAVATEX membranes and wood-fibre boards indoors and outdoors. Very high adhesion and good resistance to ageing and water. Can be exposed to the weather for max. 3 months. When gluing to porous or mineral contact surfaces, a preliminary coating of PAVABASE or PAVAPRIM is always applied.

- PAVAFIX 60: For gluing foils
- PAVAFIX 20\_40: For gluing connections
- PAVAFIX 150: For bonding ridge, valley, edge and board joints

You can find details on applications and installation guidelines in the technical or sealing brochure.

**Storage**

Cool and dry, protected from sunshine.

Acara Concepts Ltd  
 Killossery  
 Kilsallaghan  
 Swords, Co Dublin, Ireland  
 Tel IRL: +353 (0)1 8409 286  
 Tel UK: +44 (0)20 7998 1690  
 www.acaraconcepts.com  
 info@acaraconcepts.com

**PAVATEX system guarantee**

The high-performance adhesion and gluing components used in the PAVATEX system solutions ensure long-lasting, reliable system sealing in modern, multifunctional building envelopes - now also guaranteed by the new PAVATEX warranty. It offers comprehensive service if damage occurs, and therefore once again increases security for designers, installers and builders.

